2025 Mini Mayhem Rules

Car

FWD, 4 and 6 cylinder unibody cars

- 1. Any RWD car allowed, must be 4 cylinders
- 2. Any FWD car allowed, may be 4 or 6 cylinders

Build rules

The intent is to keep it simple and really easy

2 up 1 across, concrete in the door, minimum

No front hoop

Bolt a bar across the front fenders, bolted in, 1" hollow tubing, From fender to fender, in front of the rad...

Aluminum skid plate under the fuel tank, minimum 3/16"

Battery in the driver's c compartment, securely fastened to the floor of the car

Night switch for fuel injection

5 pt harness, racing seat if you want it.

Air bags must be removed from the car (not just disabled)

Fire extinguisher securely fastened, within reach of the driver

All cars MUST have one (1) front windshield bar, minimum 1/4" x 1" steel

Fuel tank or cell

- 1. Approved gas tank (Fuel Cell recommended).
- 2. Fuel tank mounted in trunk. Fuel cell to be above trunk floor but may be mounted inside spare tire well.
- 3. Stock fuel tanks may remain under the car with the following conditions.
 - a. Tank is plastic and situated in front of rear axle
 - b. Aluminum skid plate to be mounted underneath and cover entire fuel tank (Minimum 3/16")
- 6. Gas caps to be tethered and marked with car number
- 7. If a steel tank is put inside the vehicle, it must be covered with an enclosed "firewall" to protect the driver (minimum 22 gauge steel). If unsure, consult tech officials/board of directors. This is a safety issue.

Driver safety

Anything to ensure driver safety inside the cockpit is ok

Cage is ok within cockpit

Nothing to extend behind the driver

Any pipe that is added to the drivers compartment must be connected to the "cage"